

# Borne File d'attente 15.6'', 80mm



CARACTÉRISTIQUES TECHNIQUES	
<b>Certification</b>	CCC,CE, FCC ,ISO9001
<b>Cooling system</b>	Fan
<b>Dimensions</b>	450x254x1120 mm
<b>Enclosure front bezel</b>	Front bezel : Aluminum
	Back housing : cold rolled steel plate
<b>Mounting</b>	Default wall mounting bracket
<b>OS support</b>	Defult windows 10 English professional
	Microsoft ® Windows10,64bit Backlight life 50000 hrs
<b>Optional color</b>	silver & black
<b>Weight (Net)</b>	6 kg
<b>Weight (Gross)</b>	8 kg
<b>Package size</b>	45 x 14 x 35 cm
<b>CPU</b>	Intel® Core® J1900

<b>Memory</b>	4GB DDR3
<b>Storage</b>	128GB SSD
<b>Expansion Slots</b>	Full-size Mini PCI-E, Support WIFI/4G
<b>LAN</b>	100 Base-T x1
<b>I/O</b>	COM x2 (RS232)
	Power x1
	HDMI x1
	VGA x1
	USB x2
	LAN x1 (RJ-45 )
	Audio input x1
	Audio output x1
<b>Display type</b>	IPS LCD screen
<b>Display size</b>	344 x 194 mm(HxV)
<b>Resolution</b>	1920 x 1080
<b>Max. colors</b>	16.7 M
<b>Luminance cd/m<sup>2</sup></b>	250
<b>Viewing angle (H/V°)</b>	178°/178°
<b>Backlight life</b>	50000 hrs
<b>Contrast ratio</b>	1500:1
<b>Aspect ratio</b>	16:09
<b>Lifespan</b>	36 million touches at singlepoint
<b>Touch type</b>	10 Point Capacitive G+G touch screen
<b>Response</b>	<5 ms
<b>Humidity</b>	10~ 95%RH@40°C, non-condensing
<b>Ingress Protection</b>	Front panel: IP65
<b>Operating Temperature</b>	-10 ~ 50°C
<b>Storage Temperature</b>	-30 ~ 70°C
<b>Accessories</b>	Adaptor (DC12V) (cable 1 meter)
	Power plug ( cable 1.2 meter )
	K type bracket
	80 mm thermal printe